

VIKTIGT / IMPORTANT / WICHTIG / TÄRKEÄÄ



Fyll på hydraulolja innan provkörning!


Till hydraulik rekommenderas: ISO VG 32

el styrning rekommenderas: ISO VG 15/Q8 Hindemith LT

Fill with hydraulic oil before the test drive!

For hydraulics recommended: ISO VG 32

For axle steering is recommended: ISO VG 15/Q8 Hindemith LT



Füllen Sie Hydrauliköl # vor der Probefahrt!

Für Hydraulik empfohlen: ISO VG 32

Für Achslenkung wird empfohlen: ISO VG 15/Q8 Hindemith LT

Täytä hydraulisöljyä ennen koeajo!

Sillä hydraulikka suositeltavaa: ISO VG 32

Sillä akselin ohjaus on suositeltavaa: ISO VG 15/Q8 Hindemith LT

Axelstyrning / Axle steering

Hydrauliksystemet (cylinderanslutningar & slangar mm.) ska dimensioneras med minst 3/8" och så korta slangar som möjligt och max cylindertryck 150 Bar (säkerhetstryck är 160 Bar).

Dimensions for the hydraulic system (cylinder connections & hoses, etc.) should be at least 3/8" and as short hoses as possible and max cylinder pressure 150 bar (safety pressure is 160 bar).