

Troubleshooting protocol Midi

Date	Company/workshop		Your reference				
Phone		leii					
Phone		E-mail					
L Vehic	le identity						
Manufaturer/brand Registrationnur					Owner		
	HT Identity -LIGHT lådan (yellow label on the inside or outside,	always starts with 1 lotter)	Sorial n	umbor D LIGHT placts	onicbox (label on electronicbox)		
	5 Numbers			amber F-Lighti electi	onicoox (label on electronicoox)		
	errors/problem						
Check	points					ОК	Measure
1	Do an ocular inspection of the P-LI	GHT so that no dama	ige has c	occurred.			
2	Check that wiring for connection of P-LIGHT have the right cable area, min 1,5 mm ² .						
3	Check that the wiring has no dama						
4	Check that both lighting circuits are charging capacity.						
5	Check that the ground is connected to terminal 3.						
6	Check that external equipment suc						
7	Check that no external equipment is connected directly to the batteries.						
8	Run test programs and check the value the truck but the truck does not have						
9	Make sure the batteries are fully c	narged when service,	/repair is	complete.			
10	Check that the lid seal is undamag	ed.					
11	Tightening screws to lids, use hand	force – not machine	e, 8-10 N	m.			
12	Check that all functions and opera	tions work properly.	у.				
13	Check that all bolts are tightened.						

Test program value

Code	Guidevalue								
U4	min 24V	U6	min 24V	U8	0V	UC	ca 28/20°C	U1	ca 25V

